

In re ELLIOT, et al.
09/614,586

IN THE CLAIMS

Please cancel claims 24-29.

Please amend claims 1, 2, 7-11 and 17-23 as follows.

B^u
A^h
1. A heating/air-conditioning installation for a motor vehicle, comprising a thermal loop which includes a refrigerating compressor, a gas cooler, a condenser, a pressure-reducing valve, an evaporator, and a heating element, wherein the gas cooler and the heating element are grouped together into a single exchanger including a main module forming a main air/heat carrying fluid/refrigerant-fluid exchanger.

2. The installation of Claim 1, wherein the main exchanger comprises:

- at least one surface for exchanging between the air and the heat-carrying fluid flowing through the main exchanger, and
- at least one surface for exchanging between the heat-carrying fluid and the refrigerant fluid of a main loop flowing through the main exchanger.

A^h
B^u
7. The installation of Claim 1, wherein the main exchanger comprises:

- at least one surface for exchanging between the air and the refrigerant fluid, and
- at least one surface for exchanging between the heat-carrying fluid and the refrigerant fluid.

In re ELLIOT, et al.
09/614,586

8. The installation of claim 1, wherein the main exchanger includes a collector of heat-carrying fluid and a collector of the refrigerant fluid which are arranged at opposite ends of the main exchanger.

B
73
cont.
9. The installation of Claim 8, wherein an element for exchanging between the heat-carrying fluid and the refrigerant fluid comprises at least one heat-carrying fluid circuit element for making the heat-carrying fluid circulate along an outwards and return path from and to the heat-carrying fluid collector and at least one refrigerant-fluid circuit element for making the refrigerant fluid circulate along an outwards and return path from and to the refrigerant-fluid collector.

Sub
co
10. The installation of Claim 9, wherein circulation of the refrigerant fluid and of the heat-carrying fluid currents are at least partly counter to each other.

11. The installation of Claim 9, wherein the refrigerant-fluid collector exhibits an element of volume forming a refrigerant-fluid bottle for the thermal loop.

B8
17. The installation of Claim 1, wherein the thermal loop comprises an additional evaporator for operation in heating mode, and a second routing circuit in order, in heating mode, to form a heat pump the condenser of which is the main exchanger and the evaporator of which is an additional evaporator.

GH
18. The installation of Claim 1, wherein the thermal loop comprises a third routing circuit in order, in a thermal heating mode, to form a heating loop including the compressor and the main exchanger, a refrigerant-fluid outlet of the main exchanger being coupled to an inlet of the compressor.

19. The installation of Claim 18, wherein further comprising a pressure-reducing valve arranged downstream of the main exchanger.

20. The installation of Claim 1, wherein the thermal loop includes a supply device for supplying the main exchanger either with at least one of cooling water and overcooled water.

21. The installation of Claim 20, further comprising:

- an air-conditioning mode in which the main exchanger is traversed by refrigerant fluid and by overcooled water, and
- a heating mode in which the main exchanger is traversed by cooling water.

In re ELLIOT, et al.
09/614,586

B2
24
cont.

22. The installation of Claim 21, further comprising a mixing flap which, in the air-conditioning mode, is in a closed position in which the main exchanger is isolated from the airflow.

23. The installation of Claim 22, further comprising a de-misting mode in which the air-conditioning mode is activated, and in which the mixing flap is in an at least partially open position, so that the main exchanger is traversed by at least a part of the airflow.
